

revision 0, 5/01/2020

Fiber content:	<i>Polyester</i>		
Colors:	<i>WHITE</i>		
Base Type: Film Type:	Thermally bonded nonwoven Polyurethane Film		
Adhesive Type:	Blend of Polyamide & Polyester		
Base Weight: Film Weight: Total Weight:	1.25 oz/yd ² 0.80 oz/yd ² 2.05 oz/yd ²	(42 g/m ²) (27 g/m ²) (69.9 g/m ²)	±10%
Thickness:	0.009 in	(0.2 mm)	±10%
Tensile Strength	MD: Not applicable / tbd CD: Not applicable / tbd		
Elongation	MD: Not applicable / tbd CD: Not applicable / tbd		
Water Penetration:	0.07g average water penetration -- AATCC-42		
Hydrostatic Pressure:	79.6g average hydrostatic pressure -- AATCC-127		
Air Permeability:			
Hand:			
Applications:	Gowns, Protective Medical Apparel		
Special Characteristics:	Resistance of materials in protective clothing to penetration by synthetic blood -- ASTM F1670-B **		
Additional Notes:	Passes Level 2 of AAMI Surgical gown requirements		
<i>Important Notice: Preliminary specification and is subject to change without notice -All technical information is based on in-house testing.</i>			